

COLOUR ENHANCER SEALER FOR QUARTZ SURFACES



Stain protection and revitalizing treatment to be applied on agglomerations, for small and large surfaces. It is recommended primarily for kitchen tops and for all surfaces that may come into contact with foodstuffs since the product fulfils EC Regulation CE 10/2011 contact (Report no. 3882).


SOLVENT BASE

ENHANCER

APPROVED FOR FOOD CONTACT

TECHNICAL CHARACTERISTICS

Solvent based product, ready for use. Dilution is not required. The product fulfils EC Regulation CE 10/2011 for food contact (Report no. 3882).

HOW TO APPLY IT

Tools



Paintbrush, with a cloth or sponge, single brush machine.


Mode

The product can be applied by paintbrush, spraying, with a cloth or preferably with a sponge making sure to apply the amount that the material naturally absorbs evenly. A few seconds after application, remove from the surface the QUARTZ TONER in excess with a clean cloth or by using a single brush machine to prevent the formation of surface sticky films. For best results repeat the treatment after about 10-15 minutes from the first application. In case of floors, wait at least 24 hours before walking on the floor.

WHERE TO APPLY IT



QUARTZ AGGLOMERATE
glossy, honed, sanded, brushed,
flamed, rough



PLUS/ADVANTAGES

- ⊕ UNIVERSAL POSSIBILITIES OF APPLICATION ON DIFFERENT FINISHES
- ⊕ EASY TO APPLY
- ⊕ LASTING ANTI-STAIN PROTECTION
- ⊕ IT RAISES THE TONE AND COLOUR OF THE MATERIALS
- ⊕ APPROVED FOR FOOD CONTACT

TECHNICAL DATA

Density at 25 °C gr/cm ³	0,88
Appearance	opalescent liquid

COVERAGE

1L of product	20-30 m ² 215-323 sq.ft.
----------------------	--

UNTREATED

TREATED

PACKAGING

1-5-10-20-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances: If the surface is treated for the first time it is advisable to assess the effect and the adherence of the material on a sample or a hidden corner.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Click or scan
for more info