

ACTIVE PROFESSIONAL PERFORMANCE

Water-repellent sealer



Water-oil repellent sealer with a natural effect for granite, quartzite, marble, quartz-resin agglomerate.



SOLVENT BASE



NATURAL EFFECT



APPROVED FOR FOOD CONTACT

TECHNICAL CHARACTERISTICS

It is a solvent-based product, whose quick drying and easy removal of the residue make it suitable for both manual and line application.

HOW TO APPLY IT

Tools

Brush, sponge, cloth.



Method

The product must be applied on fully dry and clean surfaces. Any water and/or dust may make the treatment non-homogeneous.

The product can be applied by paintbrush, spraying, with a cloth or preferably with a sponge, making sure to apply the amount that the material naturally absorbs evenly. If applied in excess, a sticky surface film is created.

After application, remove any excess product from the surface with a clean cloth. The desired anti-stain effect is reached 24 hours after treatment.

IMPORTANT: If the surface is treated for the first time, we recommend an initial test on a sample or hidden corner.



WHERE TO APPLY IT

- NATURAL STONE
- QUARTZITE
- AGGLOMERATE



FURTHER BENEFITS

- SUPERB RESISTANCE TO STAINS
- SUPERB SPREADABILITY
- EASY RESIDUE REMOVAL

TECHNICAL DATA

Densità a 25°C g/ml	0.80
Appearance	liquid opalescent
Colour	colourless

COVER

Consumption depends greatly on the material finish and absorption

1 litre of product	20-30 m ² 215-323 sq.ft.
--------------------	--

PACK

1 litre.

HOW TO STORE IT

Under standard use and work conditions, the product is guaranteed for 24 months when properly stored away from any sources of heat, humidity and direct sunlight. Accurately close the pack after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. When the surface is treated for the first time, we recommend you assess its effect and adhesion on a sample or hidden corner.

LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the packs.

CLOSE THE CONTAINER AFTER USE.

PRODUCT FOR PROFESSIONAL USE ONLY.

The information contained in the technical sheet is updated and correct as of the date of publication. Since TENAX is unable to control or foresee the possible conditions of use of the product, the user is advised to review the information based on the specific intended use. TENAX is not liable for damages of any nature resulting from the use of the product or from having relied on the information contained in the technical sheet. TENAX is not responsible for the incorrect use of the product.



Scans to access multimedia contributions