



IT / EN

**Incollaggio strutturale  
anche in condizioni di umidità.**

***Structural bonding  
even in wet conditions.***



**NEW**

IT

**Colla bicomponente  
poli-epossidica  
solida colorata**

**MARMO - GRANITI -  
AGGLOMERATI - CERAMICA**

EN

**Solid coloured  
two-component  
poly-epoxy adhesive**

**MARBLE - GRANITE -  
AGGLOMERATES - CERAMIC**

[WWW.TENAX.IT](http://WWW.TENAX.IT)

FOLLOW US ON:



ITALY

BRAZIL

CHINA

INDIA

SPAIN

TURKEY

USA



IT

## COLLA BICOMPONENTE POLI-EPOSSIDICA

Mastice per incollare marmi, graniti, agglomerati e ceramica. Rapido, soffice, spatolabile. Si caratterizza per una buona resistenza chimica, un'ottima adesione anche su superfici umide in tempi molto brevi (30-40 min a 25°C), permettendo così una veloce processabilità degli accoppiati anche a basse temperature. Il prodotto si presenta liscio, brillante e ben lucidabile. Richiede catalizzatore in pasta  
Buona stabilità ai raggi UV.

- + Incollaggio forte
- + Veloce
- + Resistente ad alte temperature

### CARATTERISTICHE TECNICHE:

- Aspetto: Pasta Tixotropica (knifegrade) soffice
- Aspetto: Colorato
- Parte B: 100: 2-3 %
- Gel Time: 5 min
- Working Time (25°C): 25-30 min
- Range T°: 0°-110°C
- Shell Life (lontano da fonti di calore): 12 Mesi

### DOVE APPLICARLO:

- Marmo
- Granito
- Pietre
- Agglo-Marmo
- Agglo-Cemento
- Agglo-Quarzo
- Ceramica

EN

## POLY-EPOXY TWO-COMPONENT ADHESIVE

Mastic for gluing marble, granite, agglomerates and ceramics. Quick, soft, spreadable. It is characterized by good chemical resistance, excellent adhesion even on damp surfaces in a very short time (30-40 mins at 25°C), thus allowing quick processability of the paired elements even at low temperatures. The product is smooth, bright and easy to polish. Requires paste catalyst  
Good UV stability.

- + Strong bonding
- + Quick
- + Resistant to high temperatures

### TECHNICAL FEATURES:

- Appearance: soft Thixotropic paste (knife-grade)
- Appearance: Coloured
- Part B: 100: 2-3%
- Gel Time: 5 mins
- Working Time (25°C): 25-30 mins
- T° range: 0°-110°C
- Shell Life (away from heat sources): 12 months

### WHERE TO APPLY IT:

- Marble
- Granite
- Stone
- Agglo-Marble
- Agglo-Cement
- Agglo-Quartz
- Ceramic

INDOOR/OUTDOOR



INDOOR/OUTDOOR

SOLIDO



SOLID

