

IMPREGNATING SEALER IDEAL FOR QUARTZITE WORK TOPS



Solvent-based impregnating sealer excellent on glossy and polished surfaces, performing even on surfaces with higher absorption. Excellent for worktops: it makes maintenance and restoration easier.



SOLVENT-BASED



NATURAL EFFECT

TECHNICAL CHARACTERISTICS

Solvent-based, impregnating sealer, oil- and water-repellent protection. It penetrates and settles in the micro-pores of the material, protecting it from all kinds of dirt without altering its natural breathability.

Excellent protection even on highly porous materials, which are therefore completely and homogeneously protected. Designed to give high protection to quartzite worktops, it makes protection and restoration easier.

HOW TO APPLY IT

Tools



Applied by paintbrush, spraying, with a cloth or sponge.

Method

The product must be applied on perfectly dry and clean surfaces, by paintbrush, spraying, cloth or sponge.

Not very absorbent surfaces: remove any excess product from the surface with a clean cloth one minute after application. For best results, repeat the treatment after about 10-15 minutes from the first application. In rare cases it can brighten the colour of the material.

Materiali ad alto assorbimento (ad es. quarziti): dopo due ore dall'applicazione, rimuovere dalla superficie gli eventuali eccessi di prodotto con un panno imbevuto con poco prodotto. Quindi, uniformare la superficie, per evitare la formazione di residui. L'effetto antimacchia desiderato si raggiunge 24 ore dopo il trattamento. Nel caso di pavimenti, attendere 24 ore prima di camminare sulla superficie.

WHERE TO APPLY IT

- QUARTZITE**
- GRANITE**
- MARBLE**
- AGGLOMERATES**
- STONE**
- TERRACOTTA**



FURTHER ADVANTAGES

- NO HYDROCARBONS**
- IDEAL FOR WORK TOPS**
- HIGH STAIN-PROTECTION EFFECTIVE ALSO ON POROUS SURFACES**
- MAKES THE MAINTENANCE AND RESTORATION OF WORKTOPS EASIER**

TECHNICAL DATA

Density at 25°C gr/cm ³	0,800
Appearance	Opalescent liquid
Standard colour	transparent

COVER


Consumption depends greatly on the porosity of the material

1 litre of product

QUARTZITE, GRANITE, MARBLE, AGGLOMERATES, STONE, TERRACOTTA	20-30 m ² 215 -323 sq.ft.
--	---



UNTREATED



TREATED

PACK

1 litre

HOW TO STORE IT

Under standard use and work conditions, the product is guaranteed for 12 months when properly stored away from sources of heat, humidity and direct sunlight.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. When a surface is treated for the first time, it is recommended to evaluate its effect and adhesion on a sample or on a hidden corner.

LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the packs.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



[Click or scan for more info](#)